


FUJIDA C.B GREASE

Calcium Based Cup Grease



Description

FUJIDA C.B GREASE is a calcium-based grease with good water resistance property. It is highly recommended for lubricating parts of medium loading and turning speed machines. The recommended operating temperature range for NGLI 2 and 3 is below 55°C and 60°C respectively.

Features & Benefits

- Good water resistance
- Good adhesive properties
- Used in low operating temperatures

Typical Properties

Soap base	Calcium	Calcium
NLGI Classification	2	3
Color	Brownish Yellow	Brownish yellow
Worked Penetration, @ 25°C	265-295	220-250
Drop Point (°C), min	80	85
Rust Test, ASTM D1743	Pass	
Texture	Smooth, Buttery	Smooth, Tacky

Available Packings: 500gm, 2kg, 15kg, 180kg

The above product when used according to our recommendations and for the purpose for which it is intended, presents no particular hazards.

JC HADRY TRADING CO PTE LTD

- Superior anti-oxidation and anti-rust properties.

Applications

- To be used in medium and lightly loaded slow/medium speed bearings.
- Suitable for lubrication of automotive and tractors parts where operating temperatures are below 55°C and 60°C for NGLI 2 and 3 respectively.
- Can be used in both dry and moist conditions.